

Tonmind 2*15W IP Cabinet Speaker SIP-S12(M)

1. The accessory MIC is optional.
2. 2pcs 15W speaker transfers loud and excellent sound.
3. 48K OPUS Audio Codec enables excellent sound quality .
4. Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP.
5. Compatible with IP Camera VMS via ONVIF.
6. Support Pre-recorded messages.
7. Support HPPT API for alarm in transmit.



Specification:

Audio

Codec OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz

Speaker

Max SPL	99dB
Frequency Response	90Hz~18KHz
Frequency Range	500-2KHZ +-10dB 400-12KHZ +-20dB
Harmonic Distortion	0.1@1kHz
Signal to Noise Ratio	91dB

Network

Security:	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45 Support for SIP protocol for intergration with VoIP systems, intergrated with SIP/PBX.
VoIP	2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMA

Amplifier

Amplifier Description 2pcs 15W Amplifier

General

Operating Temperature	-30℃ — +60℃
Operating humidity	5%-85%
Material	Fiberboard And Birch Cold-Pressed Leather
Rate Power	2* 15W
Power Supply	100-240V ~ 50/60Hz
Installation	Wall Mounted
Dimensions	246 x 292 mm
Net Weight	4.3 KG
Languages	English
Warranty	2 years
Package Includes	IP Wall Mounted Speaker MIC (Optional) User Manual